

Downlight Integrated Driver Flush mount



Features

- Plastic housing
- Polycarbonate diffuser
- Slide switch function for colour temperature change (TSDL10WITRI only)
- High efficiency SMD chips
- Constant current driver
- IC-4
- Large terminals for easy installation
- Operating temp: -20°C to 45°C
- IP54 rated

Dimming Options

- Trailing and leading edge
- Universal


Includes



- Fixed head LED downlight
- Built-in dimmable LED driver
- 0.6m flex and plug 2 pin

Accessories

- Brushed nickel cover ring



CERTIFICATION	IP RATING	DIMMABLE
		
IC-4	COLOUR CHANGE	BOX CTN QTY
	 TSDL10WITRI only	1 30

DIMENSIONS (mm)	
	

Part No.	Voltage	Watt	PF	CCT	Ra	Lumens	Beam Angle	Lifetime hrs	Fitting Colour	Dimensions (W x H x D)mm	Cutout DØmm
TSDL10WITRI	200-240V	10W	0.9	3000K, 4000K, 5700K	80	800,940,870	90°	40,000	White	80 x 61 x 115	90-95
TSDL10WI3K	200-240V	10W	0.9	3000K	80	800	90°	40,000	White	80 x 61 x 115	90-95
TSDL10WI4K	200-240V	10W	0.9	4000K	80	940	90°	40,000	White	80 x 61 x 115	90-95
TSDL10WI5K	200-240V	10W	0.9	5700K	80	870	90°	40,000	White	80 x 61 x 115	90-95

Part No.	Description	Colour	Dimensions
TSDLRING	Downlight Brushed Nickel Ring to suit TSDL10WITRI	White	Ø115 x 3.8mm

Part No.	Model No.	VEET Status	IPART Status
TSDL10WITRI	UP-DL41C-3-10W-P3	Pending	Pending
TSDL10WI3K	UP-DL54C-3-10W-P33K	Pending	Pending
TSDL10WI4K	UP-DL54C-3-10W-P34K	Pending	Pending
TSDL10WI5K	UP-DL54C-3-10W-P35K	Pending	Pending